

LOCAL INFORMATION PROVISION

This invention relates to a system for providing a user with information on local circumstances. The system may make use of a wireless data transfer medium such as radio frequency (RF) signalling - preferably low-power RF - or other means such as infra-red signalling to transfer data between a personal device that could be carried by a user and a static device that transmits data relating to the local circumstances.

In many situations it would be useful for people to receive wirelessly information on local circumstances. For example, if a person wishes to buy from a vending machine it would be useful for him to be informed when he passes near a suitable vending machine, or if a blind person moves to an area of danger it would be useful for him to receive a warning.

Many facilities and dangers are already signed by visible, audible or tactile means. For example, shops and vending machines often bear advertising signs, pedestrian crossings may have warning buzzers and dangers such as the edges of station platforms may be marked by raised flooring. However, these are all suitable only for limited communication even to people within the normal range of utility of the circumstance being signed. For example, a vending machine may be obscured so that it cannot be seen even if it is close by and convenient for use, warning buzzers may be drowned out by loud background noises, and tactile markings are inconvenient to install and offer very limited information.

Directory and map systems exist, by means of which it is possible for a person to determine the location of facilities or dangers in a certain location. However, in order for these systems to be useful a user must know where he will be at a given time, and what his requirements will be then.

There is therefore a need for an improved system for providing information on local circumstances, especially for handicapped people.

According to the present invention there is provided a local data provision system comprising: a plurality of transmitters each located at a respective entity having a limited range of physical utility, and each transmitter being arranged repeatedly or on demand to transmit wirelessly a signal carrying data indicating the presence of the respective entity over a range substantially coterminous with the range of utility of that entity; and a personal information unit comprising a user interface for signalling information to a user and a receiver arranged to receive the availability data and to cause the user interface to signal information to the user in dependence on the received availability data.

Preferably the signal is a radio signal, for example a low power RF signal. The signal may employ a low power RF technology such as Bluetooth.

There may be a status sensor located at at least one of the entities and capable of sensing the status of the entity and causing the respective transmitter to transmit wirelessly a signal carrying data indicating the status of the respective entity.

The data indicating the presence of the respective entity is suitably termed availability data.

The signal carrying data indicating the presence of a respective entity includes data indicating the nature or type of the entity, for example as a numeric code embedded in the signal. Preferably the personal information unit is arranged to cause the user interface to signal to the user the nature or type of the entity received in the availability data.

Preferably some or all of the transmitters are static. Preferably the personal information unit is mobile.

The personal information unit suitably includes a memory capable of storing a plurality of entity types and the personal information unit is arranged to cause the user interface to signal information to the user only if the received availability data includes data indicating one of the stored types. Preferably, the personal information

unit includes input means such as a keypad for allowing a user to specify the plurality of entity types that are to be stored.

The personal information unit may be a cellular telephone, providing cellular telephone functionality in addition to that described above. Alternatively, or in addition, it may provide other functionality such as audio replay functionality.

The personal information unit is capable of non-visually alerting a user in dependence on the received availability data, for example by means of a buzzer or a vibrating device. The personal information unit may be capable of alerting a user with one of a plurality of alerts in dependence on the type indicated by received availability data.

The personal information unit is suitably a portable unit.

The present invention will now be described by way of example with reference to the accompanying drawings, in which:

figure 1 shows a schematic diagram of a local information provision system; and

figure 2 illustrates the use of the system of figure 1 in an urban setting.

The system of figure 1 comprises two principal components: an information provision unit 1, and a portable information receiver 2. The information provision unit is primarily intended to be fixed in location at the site of the circumstance on which it is to provide information. However, if that circumstance is movable then the information provision unit could move with it. The portable information receiver is intended to be carried by a user so that the user can be provided with information from nearby information provision units. The transmission range of the information provision unit may be limited, or there may be means for the information receiver to determine its distance from an information provision unit. The portable information receiver may allow a user to select the types of information he needs. By this means the user may be informed of local circumstances that are relevant to his needs.

The information provision unit 1 comprises a status sensor 11, a central processing unit 12 and a transmitter unit 13. The components 11 to 13 may, for example, be powered by a battery in the information provision unit, a connection to mains power or a solar cell.

In operation the status sensor senses at least one local factor - for example, if the information provision unit is at a pedestrian crossing it may sense whether the pedestrian crossing is currently permitting pedestrians to cross a road. Data representing the information sensed by the sensor is passed to the central processor which causes the transmitter unit 13 to transmit a corresponding signal for reception by nearby portable information receivers.

If the information provision unit is to transmit a signal that is dependant on constant rather than changeable local circumstances then the status sensor may be omitted. For example, if the information provision unit is to provide warning of the proximity of a station platform edge then the central processing unit can cause the transmitter unit to transmit an unchanging signal. In other situations the status sensor may be arranged to sense an array of local factors, for example if the information provision unit is at a vending machine then it may be arranged to sense whether the vending machine has certain products in stock. The central processing unit can then cause the transmitter unit to transmit a signal that indicates this data.

The central processing unit may be provided with a temporary random access memory and a non-volatile program memory in the normal way.

The transmitter unit may transmit signals using any suitable physical means and protocol. Examples of suitable physical means are radio and infra-red. Of these radio is preferred since it does not require line-of-sight correlation of transmitter and receiver. Low-power RF technologies such as Bluetooth are especially preferred for carrying the data. The transmitter includes dedicated circuitry for generating the signals that are to be transmitted, based on signals received from the processing unit 12, and transmission hardware such as a light-emitting diode for infra-red or a transmit chain and an antenna for RF.

If wireless data is to be received by the information provision unit, for example for contactless configuration of the unit by service personnel or for ranging as described in more detail below, then the transmitter may be a transceiver.

In one preferred embodiment the transmission power of the transmitter unit 13 is selected so that the maximum range at which its signals can be received by the information receiver 2 corresponds to the range of utility of the local circumstance that is being indicated by the information provision unit 1. For example, if the information provision unit is indicating a soft drinks vending machine then a typical range of utility may be around 200m, since few people would walk further than that to buy a soft drink from a vending machine; or if the information provision unit is indicating the end of a platform then the range of utility may be around 3m since the platform end poses no danger unless it is approached within that range.

Instead of limiting the transmission power to the useful range of the object being signalled, as described above, in another preferred embodiment the information receiver 2 is capable of estimating its distance from the transmitter of an information provision unit from which it is receiving data. This may, for example, be done by measuring at the information receiver the time delays of signals from the transmitter with respect to a master clock known to both the transmitter and the receiver; measuring at the information receiver group delay of signals from the transmitter; probing the link between the transmitter and the receiver by bi-directional communication between them (if the information provision unit and the information receiver are equipped with transceivers); or by the information provision unit transmitting data indicating its location and the information receiver being provided with other means for determining its location (for instance from local cellular telephony base-stations or the Global Positioning System (GPS)) and means for calculating the difference between the two.

If, alternatively, no means were provided for limiting the effective range of the signals from the transmitter then information receivers may easily become overburdened by unmanageable amounts of data from information provision units, including units that are so far away from the user that the data they are providing is of no interest or use to him.

The signals transmitted by the information provision unit preferably accord to a standard format so that they can easily be interpreted by information provision units. It is preferred that the signals repeat the following information:

1. Unique numeric identity of the information provision unit.
2. Type of the information provision unit. This may be a field containing that is directly descriptive of the type of the information provision unit, or a numeric type identifier that corresponds to one type from a predetermined set of types. If a predetermined set of types is used then a description of each of those types is preferably stored at the information receiver 2 to allow a user to select which of those types he requires data from, as described below
3. Status information. Such status information may provide information on the status of the local circumstances of the information provision unit as detected by its status sensor 11.

The numeric identity may be omitted if there is no need for it in a particular system, and the status information may be omitted if the information provision unit has only a single status (e.g. a platform end warning). The type information may be omitted if the system only has a single type of information provision unit; in that case the signal could be of fixed content.

The information receiver 2 comprises a receiver unit 21, a central processing unit 22 and a user interface 23. The information receiver is suitably a portable device that can easily be carried by a person. The information receiver could be integrated with another device such as a portable audio unit, a wrist watch or a cellular telephone. It could share some components (e.g. user interface or receiver unit) with such another device. In this way, the device could provide one function (e.g. playing music over headphones) which could be interrupted or supplemented over the same user interface apparatus (e.g. beeping over headphones) when an alert is called for.

The receiver unit is arranged to receive signals from information provision units 1 and to pass the resulting information to the central processing unit.

The central processing unit may be provided with a temporary random access memory and a non-volatile program memory in the normal way.

The user interface is arranged to provide information to a user in dependence on information received wirelessly from information provision units. This may, for example be by one or more of audible means, such as playing alerting tones or pre-recorded voice messages; visual means, such as flashing an indicator or displaying a stored message on a text display unit of the information receiver; or tactile means such as vibrating. The type of alerting may be preset or selected by the user to depend on the type of information that has been received. In this way the user will know what type of information provision unit he is near. For example, where different types of information provision unit are provided for blind people the alert may let the user know which of a proximity danger, a change of contour, an obstacle or a trip hazard is near.

In operation the information receiver is carried by a user. It continuously (whether uninterruptedly or intermittently) checks for signals from information provision units. If such a signal is received then the information carried by it is passed by the receiver unit to the central processing unit. In accordance with its present configuration the central processing unit may then cause the user interface to alert the user to the information. The user may then take action accordingly.

It is preferred that the user can configure the information receiver to select the data that he is to be alerted of. This may conveniently be done by means of a keypad, touch screen, mechanical knobs etc. of the user interface device. Where the information receiver stores a predetermined set of types together with a description of each of those types, the user may scroll through a display of those types and select the types on which he wishes to receive information; alternatively the desired types may be entered directly. The central processor stores the types on which information is to be received. When information from an information provision unit is received at the central processing unit the central processing unit checks whether the received information indicates that that information provision unit is one of the types on which information is desired. If it is then the user is alerted accordingly and otherwise the information is discarded. The user may also be able to select alerting on the basis of the status information provided by the data transmission units. For example, if the user wants to be alerted when he passes near a vending machine

that has a certain brand of soft drink in stock then he may configure the information receiver to filter out information from vending machines that do not have the required drink.

As indicated above, the information receiver may be capable of determining its distance from a data transmission unit. The information receiver may have additional hardware, such as a transceiver instead of a receiver, in order to accomplish this. The information receiver may also be capable of interrogating suitably equipped data transmission units to request additional status information beyond that transmitted in their standard communications. In response to such a request the transmission units return the requested information. This allows the standard communications to be kept short, reducing interference and power usage, with additional information being provided only if required.

Some specific examples of uses of the present system are illustrated in figure 2. Figure 2 shows a typical urban environment including a number of users 30 carrying information receivers 2. A number of information provision units 40-50 are provided at various locations. The information provision units in this example are as follows.

Unit 40 is located at a vending machine. It senses the status of the vending machine, including the availability of various items for purchase and repeatedly transmits that information over a range of around 200m together with an indication that the unit 40 is of a type 1 (i.e. a vending machine type).

Unit 41 is located at the end of a station platform. It repeatedly transmits a signal including its type 2 (i.e. proximity danger) over a range of around 3m to allow blind people to be alerted to the danger.

Unit 42 is located at a pedestrian crossing. It senses the status of the pedestrian crossing and repeatedly transmits that information over a range of around 50m to allow blind people nearby to be alerted to the presence and status of the crossing. The signal transmitted by unit 42 includes an indication that it is of type 3 (i.e. pedestrian crossing).

Unit 43 is located at the top of an escalator. It repeatedly transmits a signal including its type 4 (i.e. contour change) over a range of around 3m to allow blind people to be alerted to the potential hazard.

Unit 44 is located at a pillar. It repeatedly transmits a signal including its type 5 (i.e. obstacle) over a range of around 3m to allow blind people to be alerted to the potential hazard.

Unit 45 is located at the entrance to a newsagents shop. It repeatedly transmits a signal over a range of around 400m. The type of the signal is 6 (i.e. newsagents shop). If a user 30 wants to buy a newspaper he can set his information receiver to alert him when a type 6 signal is received. Thus he may be alerted when he passes near a newsagents shop. Analogous units 46 to 49 are provided at other shops, and transmit other type information.

Unit 50 is located on a bus 505. It repeatedly transmits a signal over a range of around 1000m. The type of the signal is 7 (i.e. 505 bus). If a user 30 wishes to catch a 505 bus he can set his information receiver to alert him when a type 7 signal is received. Thus he may be alerted when a 505 bus approaches.

The information receiver may be capable of making a payment by means of a credit card function. For example, the information receiver may be capable of automatically transmitting a user's credit card or other payment specification information to a receiver. This may allow the user to conveniently pay for products or services from a shop or vending machine, by transmission of the payment specification information from the information receiver (including a transceiver) to a payment accepting unit. The payment accepting unit could be integrated with the information provision unit.

In one example of a preferred implementation of the invention a user may decide that he wishes to purchase a certain soft drink from a vending machine. He configures his information receiver to alert him when information is received from a vending machine that has the soft drink available. When he is alerted that such a vending machine is nearby he approaches the vending machine and initiates a purchase transaction. He causes his information receiver to transmit his payment information

to the information provision unit of the vending machine which causes a transaction to be performed, to transfer the cost of the drink from the user's account as specified by the information receiver to the account of the operator of the vending machine. If the transaction is successful the vending machine dispenses the drink. The user then resets his information receiver so as not to receive further information on vending machines selling the soft drink.

The present invention may include any feature or combination of features disclosed herein either implicitly or explicitly or any generalisation thereof, irrespective of whether it relates to the presently claimed invention. In view of the foregoing description it will be evident to a person skilled in the art that various modifications may be made within the scope of the invention.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000